

Davit Goods Lifting & Man Riding

The Didsbury Davit consists of a single pillar and removable slewing arm that incorporates a bracket to accommodate the Didsbury 45m open-drum man-riding / goods lifting hoist.

This multipurpose Davit also accommodates chain hoists. Flush sockets, Floor mounted sockets and Wall sockets are available to meet different applications. The Davit system and all sockets have an anti-corrosion galvanized finish. BS EN ISO 1461.



PART NO:

DAVIT JIB

1.5m reach 81/1242T1.5. Weight: 20kgs
1.25m reach 81/1242T1.25. Weight 17kgs
1.0m reach 81/1242T1.0. Weight 15.5kgs

DAVIT PILLARS

Floor socket pillar 81/1243T1. Weight: 18kgs
Flush socket pillar 81/1243T2. Weight 23kgs
Wall socket pillar 81/1243T3. Weight 25kgs

DAVIT SOCKETS

Floor mounted socket 81/1244
Flush cast in socket 81/1245
Wall mounted socket 81/1246.

FEATURES:

- Portable – one Davit system can service numerous socket locations.
- Quick and easy to erect.
- Pillar installation manoeuvrable through 360 degrees.
- Designed for use with the Didsbury man-riding and goods lifting open drum 45m hoist or chain hoist.
- Requires only minimal maintenance.
- Built to meet the highest Health and Safety standards.
- Proof loaded, tested and certified for man-riding and goods lifting.

WORKING LOAD LIMIT (WLL)

Materials lifting at 1500mm reach: 330kgs at 4:1 safety factor.
Materials lifting at 1250mm reach: 400kgs at 4:1 safety factor.
Materials lifting at 1000mm reach: 500kgs at 4:1 safety factor.
Man-riding at all reaches: 127kgs at 10:1 safety factor.

DAVIT & SOCKET FINISH:

Galvanised BS EN ISO 1461